

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
16 December 2004 (16.12.2004)

PCT

(10) International Publication Number  
**WO 2004/109271 A1**

(51) International Patent Classification<sup>7</sup>: **G01N 27/447**

(21) International Application Number:  
**PCT/GB2004/002423**

(22) International Filing Date: **8 June 2004 (08.06.2004)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:  
**0313197.6 9 June 2003 (09.06.2003) GB**

(71) Applicant (*for all designated States except US*): **IMPERIAL COLLEGE INNOVATIONS LIMITED [GB/GB]**; Sherfield Building, Exhibition Road, London SW7 2AZ (GB).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **MANZ, Andreas**


[DE/DE]; ISAS-Institute for Analytical Sciences, Bunsen-Kirchhoff-Str.11, D-44139 Dortmund (DE). **ZHANG, Chao-Xuan, Dr [CN/GB]**; Department of Chemistry, Imperial College London, Sherfield Building, London SW7 2AZ (GB).

(74) Agent: **BODEN, Keith, McMurray, Dr; Fry Heath & Spence LLP, The Gables, Massetts Road, Horley, Surrey RH6 7DQ (GB)**.

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

*[Continued on next page]*

(54) Title: **FREE FLOW ELECTROPHORESIS MICROCHIP, SYSTEM AND METHOD**



(57) Abstract: Device and method for free flow electrophoresis having a microchip (1) comprising: a separation chamber (5); a plurality of separation medium inlet channels (9), a sample inlet side of the separation chamber through which a flow of a sample containing charged components is introduced into the separation chamber; a plurality of outlet channels (17) having inlets fluidly connected to another, outlet side of the separation chamber opposite the inlet side thereof, and a magnetic field unit (31) for providing a magnetic field substantially orthogonal to the flow direction of the separation medium; whereby charged components introduced into the separation chamber are deflected laterally across the separation chamber in dependence upon the charge, typically the electrophoretic mobilities or the iso-electric points, of the charged components.

WO 2004/109271 A1



(84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*